UltraLiner™

Steel Drum Liners

UltraLiner blow molded liners are CDF's best-performing drum liners. UltraLiner premium drum liners are ideal for heavy stress operations requiring maximum strength and protection. UltraLiners are designed with an ultra-thin lip to help meet UN performance standards for shipping regulated products.

Benefits

- Specifically designed for UN performance tests, each user must acquire UN certification independently
- Heavier than standard drum liners
- · Can withstand the most rigorous pumping and mixing
- Blow molded for seamless protection
- Ensures the absolute purity of your product
- Provides protection against drum corrosion
- Environment-friendly packaging, helps users to reach sustainability goals
- Reduces drum cleaning and reconditioning costs







Size

UltraLiner blow-molded liners are available for 55-gallon steel drums.

Material Choices

All liners are made in America from FDA-approved films.

UltraLiners are blow-molded from low-density polyethylene to form a smooth wall that makes them easy to install. A unique, ultra-thin contoured lip snaps over the top bead for an *ultra-secure* lid fit.

Low-density polyethylene is intended for general use and provides superb tensile strength and elongation, as well as high resistance to tears and flex cracking. Low-density polyethylene is designed for applications up to 175°F.

Anti-stat contains an internal anti-stat agent to aid in the reduction of static build-up, thus reducing dry chemical static cling and chance of ignition of flammable materials.

Custom Designs

CDF will always consider custom designs.

Most Popular Products

- PRO55M
- PRO700
- PRO800



CDF Corporation, 77 Industrial Park Road, Plymouth, MA 02360 | ©2022 CDF Corporation | 0222A

CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith. CDF products are intended for single use application. Any reuse of the liner and/or fitment voids this warranty.