# Air-Assist® Liners

The Air-Assist<sup>®</sup> liner allows the user to realize a more complete evacuation of their product. Less residual product is left inside the liner, resulting in savings to the user. Air-Assist liners are specifically designed for high-viscosity products.



#### Benefits

- Manufactured in a clean environment, using cutting-edge CDFI Smart Seal Technology<sup>™</sup> that monitors and ensures consistent, high quality seals
- Ensures the absolute purity of your product
- Specially designed for high viscosity products
- Evacuates high-viscosity products more completely than gravity flow or other systemssustainability goals
- CDF offers a variety of films, fitments and fitment placements



CDF Corporation, 77 Industrial Park Road, Plymouth, MA 02360 | ©2022 CDF Corporation | 0222 For more information or to request a free sample, please call 1-800-443-1920 or cdf1.com today!

## Air-Assist<sup>®</sup> Liners

#### CDF1 Smart Seal Technology™

Using state of the art equipment and quality control standards of the highest caliber, CDF1 Smart Seal Technology ensures the ultimate reliability of IBC form-fit liners. Proprietary CDF1 Smart Seal Technology optimizes precision and consistency through monitoring the temperature, time and pressure of every seal on every liner.

#### **Multiple Sizes**

Air-Assist liners are available for all intermediate bulk container sizes.

### **Multiple Fitment Choices**

CDF fitments are available in a variety of sizes.

#### **Material Choices**

All liners are made in America. The inside layer is made from FDA-approved films.

**EVOH** film is widely used in the food packaging industry. It is a strong, flexible, transparent film with good moisture and excellent oxygen barrier specifications.

Flexus<sup>™</sup> and Flexus HF metallocene LLDPE are for general use and provide durability and flex crack resistance.

**Tenalon™** co-extruded nylon film provides abrasion resistance, durability and strength.

The film materials used in the manufacture of our IBC liners comply with FDA Regulations 21 CFR 177.1520, CFR 175.105, 177.1390 and CFR 177.1630.

We guarantee that our liners will be constructed form the specified materials and that CDF will not knowingly use materials that are out of specification or could be adulterated. No additives are introduced during the heat-sealing process.

#### **Custom Designs**

CDF will always consider custom designs.





CDF Corporation, 77 Industrial Park Road, Plymouth, MA 02360 | ©2022 CDF Corporation | 0222

CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith. CDF products are intended for single use application. Any reuse of the liner and/or fitment voids this warranty.

CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.